

# Lijian Composite Materials Co.,LTD.

www.fiberglass-mat.com-Sale@fiberglass-mat.com-Tel :+86-13776546919-Fax:+86-25-68923190

## Fiberglass Scrim

- Substrate of APP or SBS modified bitumen membrane
- Substrate of asphalt roofing shingles
- Bitumen waterproof layer of asphalt thruway



Serials-1	FSM-100	FSM-110	FSM-140	FSM-145
Serials-2	FSM-140D	FSM-200D		

- Serials-1:Based Mat+Mesh

Codes	Mass g/m <sup>2</sup>	Linear Den sity Tex Warp:left	Mesh		Based Mat g/m <sup>2</sup>	Tensile Strength	
			ends/inch			N/50mm	
			Warp	Weft		MD	CD
FSM-100	100	68x136	7.5	4.0	40.0	800	800
FSM-110	110	68x136	10.0	5.4	40.0	900	900
FSM-140	140	68x68	7.5	7.5	50.0	1000	1000
FSM-145	145	136x136	7.5	5.4	50.0	1100	1100

- Serials-2:Base Mat+Mesh+based Mat

Codes	Mass g/m <sup>2</sup>	Linear Den sity Tex Warp:left	Mesh		Based Mat g/m <sup>2</sup>	Tensile Strength	
			ends/inch			N/50mm	
			Warp	Weft		MD	CD
FSM-140D	140	68X136	7.5	4.0	35 (2 Layers)	800	800
FSM-200D	200	136X136	7.5	5.4	40 (2 Layers)	1000	1000

- Package and Loading

Roll width Max. ≤ 2.04m

Roll Dia. 76cm

Core Dia. 76.2mm

Packed with plastic fim

Loading 114 rolls ,without pallets

- Features

3-5 times strength as the same density" Glass fiber mat"

Bigger tear strength

Straight yarns and grids makes uniform strength

Light weight,corrosion resistance

### Important Notice

Loading(uploading)-Please do not drag and drop

Please place in dry and shade

Please do not open package before use

Contact

Nanjing Lijian Composite Materials Co.,LTD.

Tel:0086-25-68923190 0086-13776546919

Fax:0086-25-68923190

Web:www.fiberglass-mat.com

E-mail:Sales@fiberglass-mat.com